
## DIMENSIONS

**Project Name:** 



# **FEATURES**

Adjustable height electrogalvanized plated steel mounting ears with cutouts for various mounting methods. Standard bars (included) are innovative and incorporate rigid formed cross sections, joist positioning tabs, integral nails, auxiliary nail holes, T-Bar slots and holes for locking bars to T-Bar using #8 self-tapping screws (by others). Bars extend 14-24". Ears will also accept Caddy Bar #517B for fast installation in T-Bar ceilings, bars extend 27".

Electronic ballast, thermally protected. UL Listed component.

Heavy gauge electrogalvanized steel junction box, prewired and grounded with easy access from below. Listed for through branch circuit wiring.

UL Listed. Specification grade open rated, pulse rated, 4KV, porcelain socket with nickel plated brass screw shell. Adjusts for 358° rotation and 35° elevation. High temperature wires connect to junction box.

Heavy gauge spun aluminum angle cut "Alzak" cone. Internal heat treated spring steel clips hold reflector tight to ceiling. White painted flange standard. Polished Flange available.

Steel housing wrap with interlocking seams for strength. Housing is top relamping with screwdriver. Housing cap is aluminum for heat transfer to ensure maximum lamp life.

#### Features

4" ARCHITECTURAL ADJUSTABLE HID

Manufactured and Listed to UL 1598, ETL and CSA standards. Suitable for Damp Locations.

Wet location under covered ceiling

#### **ORDERING INFORMATION**

Lamps and Wattage PAR20	Housing	Ballast	Reflector	Finish	Baffle	Options
20 39	PA4MHADJ20 PA4MHADJ39	E1-2 E3	4030 Spread Lens Wall Wash 4037	SCL SGC ECL WHT	BL WH	PF GSK

Electronic 120-277 volt is standard

(120-277V) E1-2 - Electronic F3 - Electronic (347V)

> Vantage reserves the right to change components, finishes or design details in any manner which does not alter the installed appearance or reduce performance and intended function.

## **REFLECTOR KIT**

### **OPEN**

1.1.1

Adjustable	e	4″ Aperture		
4030 Finish Op SCL SGC ECL WHT	Open <mark>tions</mark> Specular Clear "Alzak" Soft Glow Clear Etch Clear White Reflector	9" 4 1/2" 5 3/4"		
Options PF	Polished Flange			

Type: \_

#### SPREAD LENS WALL WASH

Adjustable		4" Aperture		
4037 Finish Option SCL SGC ECL WHT	Spread Lens Wall Wash ns Specular Clear "Alzak" Soft Glow Clear Etch Clear White Reflector	9" + 4 <sup>1</sup> / <sub>2</sub> " + 5 <sup>3</sup> / <sub>4</sub> " +		
Options PF	Polished Flange			

A. A

PF - Polished Flange GSK - Neoprene Foam Gasketing

**Options** Descriptions

▲ See Options pages for other options and finishes. Vantage recommends the use of Philips or Sylvania lamps.

EXAMPLE: PA4MHADJ39E1-2-4030-SCL