


Catalog #	Quantity
Project	
Notes	Date
Prepared by	

4" LED/Capela®

LED 4" Lensed Downlight, 700-3000 Lumens



*New construction frame & IC-Rated box sold separately

2700K 3000K 3500K 4000K



Features

Optics

Efficient optical design
15, 30, and 45 degree beam spreads
Frosted polycarbonate and Prismatic polycarbonate lenses

Controls

0-10V to 1% driver standard
0-10V to 0.1% &, Lutron, & Triac/Forward phase optional

Construction

Self-flanged or micro-flanged cold-rolled steel housing
Polyester powder coat
Torsion springs for maximum ceiling retention
Optional IC-rated up to 2,000 lumens With IC Box (NCFIC)
Optional new construction frame (NCFAC)

Electrical

Advanced QuickConnect for easy installation
High flux CoB array
80+ CRI standard, 90+ CRI optional
2700K, 3000K, 3500K, 4000K standard
High- performance Dim-to-Warm optional
70% lumen maintenance at 50,000 hours
120 – 277V Universal Input standard

Listings

Tested according to LM-79 and LM-80 standards
ETL certified to UL 1598 and UL 8750 requirements
Energy Star certified
Suitable for damp locations; Wet location under covered ceiling;
Not recommended for outdoor use
Buy American Act

Warranty

5-year limited warranty on LED components
Warranty terms located at: <http://vantageltg.com/product-warranty/>

Ordering Information

EXAMPLE: V4CERU-20DTW-L4074P-SCL-M-WHT-NCFIC-DL-2

Series	Voltage*	Lumens	Kelvin	Reflector	Finish	Distribution	Flange Finish	Frame	Options*
V4CER	U - 120V-277V 1 - 120 V 3 - 347V	07 - 700 13 - 1300 20 - 2000 30 - 3000	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K DTW - Dim-to-Warm (3000K-1800K)	L4071FR L4074P	SCL Specular Clear	N - 15° M - 30° W - 45°	WHT BLK	NCFAC New Construction Frame NCFIC New Construction Frame w/ IC-RATED Box RMDL Remodeler	DL-2 LDE1 L3D0 LDE5 EM HCR TDM XDM

*Voltage Notes

- 1 - Lutron Drivers - please consult factory
- 3 - Step-down Transformer

*Options Notes

DL-2 - Lutron 2 wire Hi-Lume Dimming Driver
LDE1 - Lutron EcoSystem Fade-to-Black™
L3D0 - Hi-Lume Premier 0.1% EcoSystem
LDE5 - 5% Dimming EcoSystem
EM - Emergency battery back-up. Remote test button & indicator Light
HCR - 90+ CRI
LDE1 - Lutron EcoSystem Fade-to-Black™
TDM - Triac Dimming Driver (Forward Phase). Only available in 120V only
XDM - 0-10V 0.1% Dimming



*Lens Options Notes

1FR - Frosted Polycarbonate
4P - Prismatic Polycarbonate



Vantage reserves the right to change components, finishes or design details in any manner which does not alter the installed appearance or reduce performance and intended function. | Capela® is a registered trademark of Vantage Lighting.

Dimensional Data: LED 4" Enclosed Downlight


Remodeler (standard) Ceiling Cut Out 4.875"



New Construction Frame (FCFAQ) Ceiling Cut Out 4.875"




NCFIC (IC-RATED) Ceiling Cut Out 4.875"



RMDL
(standard)





NCFQA
(new construction frame)




Photometric Data: LED 4" Enclosed Downlight

15° Distribution

Test Number
PHM-RPT-171110-D14
Model
V4CERU-0735K-N
Lumens
764.24
Efficacy
76.96
SC
0.9956

Cone of Light



	Center Beam fc	Beam Width	
1.7	515	1.0	1.0
3.3	137	1.9	1.9
5.0	59.6	2.9	2.9
6.7	33.2	3.9	3.9
8.3	21.6	4.8	4.8
10.0	14.9	5.8	5.8

Candela Table



Degrees Vertical	Candela
0.0	1489
5.0	1323
10.0	1045
15.0	791
20.0	583
25.0	413
30.0	274
35.0	165
40.0	96
45.0	57
50.0	38
55.0	28
60.0	22
65.0	18
70.0	14
75.0	11
80.0	9
85.0	5
90.0	2

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	526.4	68.9
0-40	635.3	83.1
10-60	712.3	93.2
60-90	36.5	4.8
0-90	748.8	98.0
90-180	15.4	2.0
0-180	764.2	100.0

30° Distribution

Test Number
PHM-RPT-171110-D12
Model
V4CERU-1335K-M
Lumens
1277.64
Efficacy
94.92
SC
0.9089

Cone of Light



	Center Beam fc	Beam Width	
1.7	749	1.2	1.1
3.3	199	2.2	2.2
5.0	86.6	3.4	3.4
6.7	48.2	4.5	4.5
8.3	31.4	5.6	5.5
10.0	21.7	6.8	6.8

Candela Table



Degrees Vertical	Candela
0.0	2165
5.0	2018
10.0	1705
15.0	1333
20.0	998
25.0	721
30.0	485
35.0	298
40.0	173
45.0	102
50.0	65
55.0	45
60.0	34
65.0	26
70.0	20
75.0	15
80.0	11
85.0	8
90.0	3

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	880.9	68.9
0-40	1075.1	84.1
10-60	1204.3	94.3
60-90	51.5	4.0
0-90	1255.8	98.3
90-180	21.9	1.7
0-180	1277.6	100.0

45° Distribution

Test Number
PHM-RPT-171110-D13
Model
V4CERU-1335K-W
Lumens
1257.93
Efficacy
93.59
SC
0.9041

Cone of Light



	Center Beam fc	Beam Width	
1.7	603	1.4	1.4
3.3	160	2.7	2.7
5.0	69.7	4.1	4.1
6.7	38.8	5.5	5.5
8.3	25.3	6.9	6.8
10.0	17.4	8.3	8.2

Candela Table

Degrees Vertical	Candela
0.0	1743
5.0	1673
10.0	1504
15.0	1261
20.0	1001
25.0	743
30.0	507
35.0	322
40.0	194
45.0	116
50.0	71
55.0	47
60.0	33
65.0	23
70.0	17
75.0	12
80.0	8
85.0	6
90.0	3

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	839.5	66.7
0-40	1050.0	83.5
10-60	1294.8	95.0
60-90	41.3	3.3
0-90	1236.1	98.3
90-180	21.9	1.7
0-180	1257.9	100.0

CAPELA Lumen Output Multipliers

CRI	MULTIPLIER
80	1
90	0.82

KELVIN	MULTIPLIER
4000K	1.036
3500K	1
3000K	0.974
2700K	0.94

FINISH	MULTIPLIER
SCL	1
SGC	0.95
WHT	0.87

Photometric Data: LED 4" Enclosed Downlight

Lumens/Wattage

Nominal Lumens	Wattage*	CCT
700	7.56	3500K
1300	12.7	3500K
2000	19.6	3500K
3000	27.4	3500K
*Actual Wattage/Lumens may vary.		

Emergency Lumen Output

Nominal Lumens	Wattage*	CCT*
300	2.5	3500K
*Actual Wattage/Lumens may vary.		

Dim-to-Warm Performance

Nominal Lumens	100%				1%			
	Wattage	CCT	CRI	R9	Wattage	CCT	CRI	R9
700	9.7	3100	95	85	2.9	1800	95	85
1300	13.2	3100	95	85	3.3	1800	95	85
2000	20.3	3100	95	85	3.8	1800	95	85