


Part #	Prepared By
Project	Notes
Type	
Date	



4" C-Class, LED Adjustable

Open Round, 700-1300 lumens - Shallow Housing



Description

C-Class small-aperture shallow downlights provide efficient performance and a modern aesthetic at a value. New Construction, IC-Rated and Remodeler housing options available. Open C-Class adjustable downlights provide 30° vertical and 360° horizontal adjustment ranges.

Features & Construction

ELECTRICAL SYSTEM

- 700, 1300 lumens
- 2700K - 4000K CCT
- 80 CRI with 3 SDCM color consistency (+90 CRI optional)
- Standard 0-10V 10% dimming driver; optional drivers available
- 120V - 347V input volts
- Minimum 50,000 hour lifetime at L70
- -20°C to 30°C Ambient Operating Temperature Range

OPTICS

- Narrow, Medium, Wide & Flood distributions
- Optical mixing dome for soft luminance
- Soft Glow Clear, White Matte finishes
- 30° vertical, 360° horizontal adjustability

FRAME & MOUNTING

- Stainless steel spring torsion retaining ears
- Advanced Quick Connect for easy installation
- Driver/junction box listed for through branch wiring
- Optional New Construction Frame with T-Bars
- Optional IC-Rated Frame with T-Bars

Listings

- ETL certified to UL 1598 and UL8750 requirements
- Tested according to LM-79 and LM-80 standards
- Suitable for damp locations; Wet location under covered ceiling
- Buy American Act (BAA)

Warranty & Notes

- 5-year limited warranty on LED module and driver
- www.vantageltg.com/product-warranty
- Photometric tests performed by an accredited NVLP facility and in accordance to IESNA LM-79-2008 testing procedures
- Insulation cannot be in contact with non-IC versions.

Lumens

Nominal Lumens	Wattage
700	7.7
1300	14.2
All measured at 3500K with a standard medium distribution *Actual Wattage/Lumens may vary.	

Ordering Information

EXAMPLE: A4VOCLEDADJU-0735K-C400-SGC-MD-WHT-NCFAQ-HCR

A4VOCLEDADJ		-			-	C400	-		-		-		-		-	
Series	Voltage	Lumens	Kelvin (CCT)	Reflector	Reflector Finish	Distribution	Flange Finish	Frame	Options*							
A4VOCLEDADJ	1 - 120V 2 - 277V 3 - 347V* *Step-down transformer	07 - 700 13 - 1300	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K	C400 Open Reflector	SGC Soft Glow Clear WHT White Matte* *FL distribution available in WHT only	NW - Narrow 16° MD - Medium 26° WE - Wide 39° FL - Flood 90°	WHT White Matte BLK Black	NCFAQ New Construction Frame w/ Advanced Quick-Connect NCFIC New Construction Frame w/ IC Box RMDL Remodeler	SDM TDM XDM ZDM DL-2 LDE1 LDE5 PEQ0 HCR EM							

*Options Notes

SDM - 0-10V 10% dimming driver (standard)
 XDM - 0-10V 0.1% dimming driver
 ZDM - 0-10V 1% dimming driver
 TDM - Triac (Forward-Phase) dimming driver
 DL-2 - Lutron 2-Wire Hi-Lume dimming driver
 LDE1 - Lutron EcoSystem Digital Fade-to-Black 1% dimming driver
 LDES - Lutron 5-Series EcoSystem 5% dimming driver
 PEQ0 - Lutron EcoSystem Fade-to-Black 0.1% dimming driver
 HCR - High CRI, 90+
 EM - Remote emergency battery back-up, remote test button & indicator light



Narrow - NW



Medium - MD
Wide - WE



Flood - FL

Vantage reserves the right to change components, finishes or design details in any manner which does not alter the installed appearance or reduce performance and intended function.

P. 2 of 3

4" C-Class, LED Adjustable

Open Round, 700-1300 lumens



Photometry

NARROW - NW 16° 1330K

Model
A4VOCLEDADJ1-NW-0730K


Lumens
1,750

Watts
14.4

Efficacy
121.53

SC
0.38

Candela Curve



Cone of Light

Mounting Height AFF	FC at Center on Floor	Beam Diameter
8.0 '	70 fc	3.1 '
10.0 '	45 fc	3.8 '
12.0 '	31 fc	4.6 '
14.0 '	23 fc	5.4 '
16.0 '	17 fc	6.1 '
20.0 '	11 fc	7.7 '
24.0 '	8 fc	9.2 '
30.0 '	5 fc	11.5 '

Candela Table

	0.00°
0.00°	4,463
5.00°	3,862
10.00°	2,535
15.00°	1,512
20.00°	1,044
30.00°	700
40.00°	561
50.00°	113
60.00°	13
70.00°	1
80.00°	0
90.00°	0

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0° - 30°	1,064	61%
0° - 40°	1,446	83%
0° - 60°	1,745	100%
60° - 90°	6	0%
0° - 20°	699	40%
20° - 50°	1,016	58%
50° - 70°	35	2%
70° - 90°	0	0%
0° - 90°	1,750	100%
90° - 180°	0	0%
Total	1,750	100%

Spacing Criterion

Height	Spacing	Light Level*
8 ft	3.0 ft	~ 70 fc
10 ft	3.8 ft	~ 45 fc
12 ft	4.6 ft	~ 31 fc
8 ft	2.3 ft	~ 124 fc
10 ft	2.8 ft	~ 79 fc
12 ft	3.4 ft	~ 55 fc
8 ft	1.5 ft	~ 279 fc
10 ft	1.9 ft	~ 179 fc
12 ft	2.3 ft	~ 124 fc

* approximate direct light level at floor based on spacing criterion overlap

MEDIUM - MD 26° 1330K

Model
A4VOCLEDADJ1-MD-1330K


Lumens
1,770

Watts
14.4

Efficacy
122.92

SC
0.62

Candela Curve



Cone of Light

Mounting Height AFF	FC at Center on Floor	Beam Diameter
8.0 '	37 fc	5.5 '
10.0 '	24 fc	6.9 '
12.0 '	17 fc	8.3 '
14.0 '	12 fc	9.7 '
16.0 '	9 fc	11.0 '
20.0 '	6 fc	13.8 '
24.0 '	4 fc	16.6 '
30.0 '	3 fc	20.7 '

Candela Table

	0.00°
0.00°	2,387
5.00°	2,224
10.00°	1,878
15.00°	1,515
20.00°	1,205
30.00°	770
40.00°	581
50.00°	140
60.00°	22
70.00°	4
80.00°	0
90.00°	0

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0° - 30°	1,024	58%
0° - 40°	1,436	81%
0° - 60°	1,762	100%
60° - 90°	8	0%
0° - 20°	601	34%
20° - 50°	1,121	63%
50° - 70°	47	3%
70° - 90°	1	0%
0° - 90°	1,770	100%
90° - 180°	0	0%
Total	1,770	100%

Spacing Criterion

Height	Spacing	Light Level*
8 ft	5.0 ft	~ 37 fc
10 ft	6.2 ft	~ 24 fc
12 ft	7.4 ft	~ 17 fc
8 ft	3.7 ft	~ 66 fc
10 ft	4.7 ft	~ 42 fc
12 ft	5.6 ft	~ 29 fc
8 ft	2.5 ft	~ 149 fc
10 ft	3.1 ft	~ 95 fc
12 ft	3.7 ft	~ 66 fc

* approximate direct light level at floor based on spacing criterion overlap

WIDE - WE 39° 1330K

Model
A4VOCLEDADJ1-WE-0730K


Lumens
1,779

Watts
14.4

Efficacy
123.54

SC
0.83

Candela Curve



Cone of Light

Mounting Height AFF	FC at Center on Floor	Beam Diameter
8.0 '	28 fc	8.8 '
10.0 '	18 fc	11.0 '
12.0 '	12 fc	13.2 '
14.0 '	9 fc	15.3 '
16.0 '	7 fc	17.5 '
20.0 '	4 fc	21.9 '
24.0 '	3 fc	26.3 '
30.0 '	2 fc	32.9 '

Candela Table

	0.00°
0.00°	1,766
5.00°	1,696
10.00°	1,550
15.00°	1,391
20.00°	1,217
30.00°	877
40.00°	624
50.00°	153
60.00°	29
70.00°	7
80.00°	0
90.00°	0

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0° - 30°	973	55%
0° - 40°	1,416	80%
0° - 60°	1,758	99%
60° - 90°	20	1%
0° - 20°	525	30%
20° - 50°	1,183	67%
50° - 70°	65	4%
70° - 90°	5	0%
0° - 90°	1,779	100%
90° - 180°	0	0%
Total	1,779	100%

Spacing Criterion

Height	Spacing	Light Level*
8 ft	6.6 ft	~ 28 fc
10 ft	8.3 ft	~ 18 fc
12 ft	10.0 ft	~ 12 fc
8 ft	5.0 ft	~ 49 fc
10 ft	6.2 ft	~ 31 fc
12 ft	7.5 ft	~ 22 fc
8 ft	3.3 ft	~ 110 fc
10 ft	4.1 ft	~ 71 fc
12 ft	5.0 ft	~ 49 fc

* approximate direct light level at floor based on spacing criterion overlap

FLOOD - FL 90° 1330K

Model
A4VOCLEDADJ1-FL-1330K


Lumens
1,801

Watts
14.4

Efficacy
125.07

SC
1.14

Candela Curve



Cone of Light

Mounting Height AFF	FC at Center on Floor	Beam Diameter
8.0 '	16 fc	16.3 '
10.0 '	10 fc	20.3 '
12.0 '	7 fc	24.4 '
14.0 '	5 fc	28.5 '
16.0 '	4 fc	32.5 '
20.0 '	2 fc	40.7 '
24.0 '	2 fc	48.8 '
30.0 '	1 fc	61.0 '

Candela Table

	0.00°
0.00°	996
5.00°	973
10.00°	929
15.00°	887
20.00°	847
30.00°	763
40.00°	674
50.00°	235
60.00°	118
70.00°	68
80.00°	18
90.00°	0

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0° - 30°	720	40%
0° - 40°	1,169	65%
0° - 60°	1,654	92%
60° - 90°	147	8%
0° - 20°	347	19%
20° - 50°	1,172	65%
50° - 70°	227	13%
70° - 90°	55	3%
0° - 90°	1,801	100%
90° - 180°	0	0%
Total	1,801	100%

Spacing Criterion

Height	Spacing	Light Level*
8 ft	9.1 ft	~ 16 fc
10 ft	11.4 ft	~ 10 fc
12 ft	13.7 ft	~ 7 fc
8 ft	6.8 ft	~ 28 fc
10 ft	8.5 ft	~ 18 fc
12 ft	10.3 ft	~ 12 fc
8 ft	4.6 ft	~ 62 fc
10 ft	5.7 ft	~ 40 fc
12 ft	6.8 ft	~ 28 fc

* approximate direct light level at floor based on spacing criterion overlap

Vantage reserves the right to change components, finishes or design details in any manner which does not alter the installed appearance or reduce performance and intended function.