



Commercial CYLINDERS

NEW

2000
LUMEN MAX
4"X12"

5000
LUMEN MAX
6"X14"

Commercial Value, High-Quality Light

- LUMENS: 1100, 1500, 2000, 3000, 4000 & 5000
- KELVIN: 2700K, 3000K, 3500K, 4000K, & 5000K
- Triac, 0-10V 1% & 0-10V 10% Dimming
 - High CRI 90+ Available
- Universal 120V-277V Input Volts
- 50,000 Hour Minimum Lifetime at L70



Commercial CYLINDERS



Reduce Cost & Add Value To Any Project

NEW

NEW

4"x12"

1100-2000
LUMENS

6"x6"

1100-2000
LUMENS

6"x10"

1100-2000
LUMENS

6"x14"

1100-5000
LUMENS

SPECIFICATIONS

SERIES	LUMENS	KELVIN	CYLINDER FINISH	DIMMING SOLUTIONS	ADDITIONAL OPTIONS
4"x12" - VP412FCR	11 - 1100	27K - 2700K	BLK - Black Matte	TDM - Triac	HCR - High CRI 90+ Min.
4"x12" - VC412FCR	15 - 1500	30K - 3000K	WHT - White Matte	ZDM - 0-10V 1%	REM - Remote Emergency
6"x6" - VP66FCR	20 - 2000	35K - 3500K	CS - Silver	SDM - 0-10V 10% (standard)	CCK-72 - Cord & Cable Mount
6"x6" - VC66FCR	30 - 3000*	40K - 4000K			
6"x10" - VP610FCR	40 - 4000*	50K - 5000K			
6"x10" - VC610FCR	50 - 5000*				
6"x14" - VP614FCR					
6"x14" - VC614FCR					

*Available with 6"x14"



BAA Compliant
Made in Rhode Island, USA

MOUNTING SOLUTIONS

VP - Pendant
CCK - Cord & Cable
VC - Ceiling/Surface