



LuxifyTM

Performance High Bays



Luxify™

Performance High Bays

The all new Luxify™ Performance High Bays offer high outputs of up to 20,000 lumens and efficiencies of up to **144 LPW**. The new design brings performance and style to projects in need of a High Bay with efficiency and beautiful aesthetics.

Vantage Luxify™ High Bays are available with flat and conical polycarbonate lenses. Aluminum shades come standard with a high reflective white painted inner shade. Use a custom color for the exterior of the shade and housing to provide a unique decorative appearance. Add a wire guard to 16" models for increased durability or a retro aesthetic.



AGVBLED12



LGVLED12



AGVBLED16



LGVLED16

12"

UP TO
15,000
LUMENS

Open Polycarbonate Shade
Lensed Polycarbonate Shade
Open Aluminum Shade



16"

UP TO
20,000
LUMENS

Open Polycarbonate Shade
Lensed Polycarbonate Shade
Open Aluminum Shade
Decorative Wire Guard



20,000 Lumen High-Output LED Light Engine

Delivering up to 144 LPW and tight color binning control within 3-step MacAdam Ellipses, ensuring efficient and quality lighting solutions for a multitude of applications. Available range from 5,000 up to 20,000 Lumens

High-Performance Features

Offering flicker free lighting with features such as high-output LED, multiple distributions and lensing, 0-10V 10%, 1%, Triac and DMX dimming, 90+ high CRI, 3000-5000 Kelvin options and a large lumen range.

Expanded Applications

Offering Triac dimming up to 10,000 lumens, the Luxify™ Performance High Bays can easily replace traditional light source High Bays and provide a similar aesthetic. Mounting options include Pendant, Cord & Cable and Hook for ease of install in a variety of applications.

UP TO
144
LPW



New Sleek Design

The Luxify™ Performance High Bays are designed to offer retro styling with the benefit of LED lighting to add value while reducing the annual energy costs.

Finishes & Mounting



LGVBLE16
Pendant
Black Matte



AGVBLED16
Pendant
Bronze



AGVBLED16
Cord & Cable
Silver



LGVBLE16
Hook Mount
White Matte

High Bay Specs

Lumens

50 - 5000
60 - 6000
80 - 8000
100 - 10000
120 - 12000
150 - 15000
175 - 17500*
200 - 20000*

Kelvin

30K - 3000K
35K - 3500K
40K - 4000K
50K - 5000K

Dimming

SDM - 10% 0-10V (Standard)
ZDMHL - 1% 0-10V
DTDHL - 0.1% 0-10V
TDMHL - Triac Dimming
DMX - DMX Dimming

Mounting

P - Pendant (Standard)
CCK - Cord & Cable
H - Hook Mount

Shade

AGV - Aluminum
LGV - Polycarbonate

Shade Accessories

BL - Flat Clear Lens
CL - Conical Clear Lens
WG - Wire Guard**

* Lumen levels only available on BLED16 with LGV shade option

** WG - Wire Guard only available on BLED16



Proudly designed and manufactured
in Rhode Island USA.

Luxify™ Performance High Bays
are Buy American Act (BAA) Compliant

VANTAGELTG.COM