
6" Aperture

6INC

DIMENSIONS



FEATURES

Electrogalvanized steel frame components with spring steel reflector clips for fast assembly of reflector. Innovative, rigid bar hangers incorporate formed cross sections, joist positioning tabs, integral nails, auxiliary nailholes, T-Bar slots and holes for locking bars to T-Bar using #8 self-tapping screws (supplied by others). Bars extend 14~24″. Frame will also accept Caddy Bar #517B for fast installation in drop-in ceilings, bars extend 27″

Heavy gauge electrogalvanized steel junction box, prewired and grounded with easy access from below. Listed for through branch circuit wiring. Thermal cutout provided.

Aluminum socket cup with spring steel snap-in clips for fast assembly. *UL Listed* medium base porcelain socket, with nickel plated brass screw shell.

Heavy gauge spun aluminum low iridescent reflector with self trimming white painted flange. Polished Flange available.

REFLECTOR KIT

OPEN

6000 Open

Finish Options

SCL Specular Clear "Alzak"

SGC Soft Glow Clear

ECL Etch Clear

WHT White Reflector

Polished Flange

Polished Flange

PF

6" Aperture

6050 Open Baffled

Finish Options

Specify reflector finish option - see above, then add baffle finish color

BL Black Baffle

WH White Baffle

WALL WASH

6" Aperture

6102 Wall Wash

Finish Options

SCL Specular Clear "Alzak"

SGC Soft Glow Clear

ECL Etch Clear

Options

Features



Manufactured and Listed to UL 1598, ETL and CSA standards. Suitable for Damp Locations. Wet location under covered ceiling.

ORDERING INFORMATION

Lamps and Wattage	Housing	Reflector	Finish	Baffle	Options
150 A21 (MAX) 100 PAR30 90 PAR38	6INC 6INC-GU24	6000 Baffled 6050	SCL SGC ECL WHT	BL WH	PF GSK 277 SD 347 SD
		Wall Wash 6102			

Options Descriptions

PF - Polished Flange GSK - Neoprene Foam Gasketing 277V SD - Step Down Transformer 347V SD - Step Down Transformer

Vantage reserves the right to change components, finishes or design details in any manner which does not alter the installed appearance or reduce performance and intended function.

▲ See Options pages for other options and finishes. Suitable for use with LED lamps.

EXAMPLE: 6INC-6000-SCL