
### DIMENSIONS

**Project Name:** 



### **FEATURES**

Adjustable height electrogalvanized plated steel mounting ears with cutouts for various mounting methods. Standard bars (included) are innovative and incorporate rigid formed cross sections, joist positioning tabs, integral nails, auxiliary nailholes, T-Bar slots and holes for locking bars to T-Bar using #8 self-tapping screws (supplied by others). Bars extend 14"-24". Ears will also accept Caddy Bar #517B for fast installation in T-Bar ceilings, bars extend 27".

Heavy gauge electrogalvanized steel junction box, prewired and grounded. Listed for through branch circuit wiring. Thermal cutout provided.

Heavy gauge spun aluminum reflector with self trimming white painted flange. Polished Flange available.

Extruded aluminum heat sink socket cup with Zinc plated steel hardware and spring clips for fast assembly. UL Listed medium base porcelain socket, with nickel plated brass screw shell.

Electrogalvanized plated steel frame.

# **REFLECTOR KIT**

### OPEN

			6″ Aperture
6000 Finish Option	Open 15	8 3/4″	Vera
SCL SGC ECL WHT	Specular Clear "Alzak" Soft Glow Clear Etch Clear White Reflector		
Options			↑ 1 1/2  ↓
PF	Polished Flange		

Type: \_


### **OPEN BAFFLED**

6050 Open Baffled Finish Options Specify reflector finish option - see above, then add baffle finish color BL Black Baffle		8 <sup>3</sup> /4″		
WH WALL	White Baffle			

6" Aperture

6" Aperture

#### 6102 Wall Wash **Finish Options** SCL Specular Clear "Alzak" Soft Glow Clear SGC ECL Etch Clear WHT White Reflector Options DWW Double Wall Wash PF Polished Flange



PAR LAMPS NOT AVAILABLE FOR WALL WASH

**ທ**ຸ

## Features

Manufactured and Listed to UL 1598, ETL and CSA standards. Suitable for Damp Locations.

Wet location under covered ceiling

### **ORDERING INFORMATION**

Lamps and Wattage	Housing	Reflector	Finish	Baffle	Options
100 PAR38∻ (MAX) 100 PAR30∻ 75 PAR16 ✤ Long Neck Only	A6INC A6INC-GU24	6000 Baffled 6050 Wall Wash 6102	SCL SGC ECL WHT	BL WH	R PF PR DWW GSK 277V SD 347V SD

**Options Descriptions** R - Remodeler PF - Polished Flange PR - Plaster Ring

GSK - Neoprene Foam Gasketing 277V SD - Step Down Transformer 347V SD - Step Down Transformer

EXAMPLE: A6INC100-6000-SCL

Vantage reserves the right to change components, finishes or design details in any manner which does not alter the installed appearance or reduce performance and intended function. ▲ See Options pages for other options and finishes. Suitable for use with LED lamps.